



Features & Specifications

information current as of September 2010.

1 Construction

Manufactured of high pressure injection-molded high density polyethylene resin.
Wall thickness: floor .200", side walls .135"

2 Dimensions, Capacity, Weight & Shipping

Dimensions: 24" width, 24" depth, 36" height

Capacity 55 U.S. gallons/208 litres

Weight (empty): 17 pounds

Shipping: nested lids and barrels ship at 60 units per pallet/1440 units per 53' trailer.

3 Recycled Content

Recycled content varies with resin color. Minimum 50% recycled content, maximum 75%.

4 Warranty

Warranted against main body and lid manufacturing defects for a period of **five years** from date of purchase.

5 Shape

Square shape facilitates flush installation against walls and in corners. Rounded corners offer easy cleaning, enhanced strength, and injury prevention.

6 Spigot/Faucet

Factory-drilled primary spout hole (A) is elevated to accommodate watering cans under spout.

Three additional spigot mount points (B) provided (at bottom center of each side wall) for end users to drill and install additional faucets if desired.

7 Stainless Steel Mesh

Rust-resistant, black powder-coated stainless steel mesh (C) filters debris and resists pests and insects. If care is exercised, end users can remove the mesh for thorough cleaning with a simple flat-head screwdriver. Black powder coating resists staining and maintains appearance.

8 Overflow/Daisychain

Overflow side is user-selectable (ships with water-tight molded knock-outs in place). Easily daisychained for multi-barrel installations. Semi-recessed/protected overflow spout locations prevent injury and facilitate clean, attractive installations.

DISTINGUISHING FEATURES

- elevated spout
- removable, non-staining steel mesh
- square shape
- FOUR spigot mount points

